

Specifications

SMART Board® 6065 HD interactive display

Model SBID-6065-HD

Overview

The SMART Board® 6065 HD interactive display combines SMART's proprietary DVIT® (Digital Vision Touch) technology with the premium touch experience of SMART Learning Suite, including SMART Notebook®, SMART lab™, SMART amp® and SMART response 2™ software.

The 65" high-definition LED display provides image clarity and wide viewing angles. With the Pen ID™ feature, you can assign different appearances to the two pens and write or draw over any application in digital ink.


Object Awareness™ allows you to perform mouse functions with your finger, write in digital ink with the pen, and erase with your palm or eraser—all without switching tools or modes. You can use a variety of gestures in applications, and two users can write or draw at the same time.

See education.smarttech.com for more information.



Dimensions and weights¹

Dimensions



Weight

153 lb. (69.3 kg)

Shipping dimensions (including pallet)

67 5/8" × 49 3/8" × 11 7/8"
(171.8 cm × 125.3 cm × 30.3 cm)

Shipping weight

187 lb. (85 kg)



As an ENERGY STAR® certified signage display, the SMART Board 6065 HD interactive display meets strict energy efficiency guidelines set by the U.S. Environmental Protection Agency and Department of Energy.

¹All dimensions ± 1/8" (0.3 cm). All weights ± 2 lb. (0.9 kg).

Hardware

Interaction

Touch technology	DViT technology
Multitouch capabilities	8 touches ²
Object Awareness	Behavior adjusts automatically to the tool or object you're using, whether it's a pen, finger, eraser or palm.
Pen ID	Two people can write independently and simultaneously, using different colored ink.

Display

Type	LED
Aspect ratio	16:9
Optimal resolution	1920 × 1080 at 60 Hz
Horizontal frequency	26.97–75.0 kHz
Vertical frequency	23.9–60.32 Hz
Contrast ratio (typical)	5000:1
Brightness (maximum)	365 cd/m ²
Pixel dimensions	0.744 mm × 0.744 mm
Gamut	72% of NTSC
Viewing angle	178°
Response time (typical)	8 ms

Presence detection Presence detection sensor on the bottom frame

Audio 10 W integrated speakers (×2)

Noise level <35 dBA

Included cables and accessories 8' (2.4 m) country-specific power cable
16' 5" (5 m) USB cable
Pen (×2)

Mounting holes For a standard VESA® 300 mm × 400 mm mounting plate
Lower mounting holes 13 3/4" (35 cm) from the bottom of the interactive display

Mounting bracket depth Minimum depth of 1 5/8" (4.2 cm) for all components on the back of the interactive display to clear the wall

²Requires SMART Product Drivers to be installed. Some applications might not support 8 touches.


Connectors

Connector panel	OPS slot HDMI®1 input connectors HDMI in USB Type-B HDMI2 input connectors HDMI in USB Type-B DisplayPort input connectors DisplayPort in USB-Type-B Stereo 3.5 mm out RS-232 in
Bottom	USB 2.0 Type-A
Back	AC power inlet
HDCP support	Version 1.4

Installation requirements

Interactive display	See the <i>SMART Board 6000 series interactive displays with iQ installation and maintenance guide</i> (smarttech.com/kb/171167)
Room computers and guest laptops	See the SMART Notebook software release notes
Mini-computers	
General requirements	See the SMART Notebook software release notes
Dimensions	Smaller than 10" × 10" × 2" (25.4 cm × 25.4 cm × 5.1 cm)
Weight	Less than 10 lb. (4.5 kg)
Mounting	VESA 75 mm × 75 mm or 100 mm × 100 mm mounting pattern

Cable requirements

HDMI	Maximum length: 23' (7 m) <hr/>  NOTES <ul style="list-style-type: none"> • Use only certified HDMI cables that have been tested to support the performance standard you require. • The performance of cables longer than 23' (7 m) is highly dependent on the cable's quality. <hr/>
DisplayPort	DisplayPort 1.2 compliant or better Maximum length: 23' (7 m)

USB	Maximum length: 16' (5 m)
Important	Using cables that exceed these maximum lengths can produce unexpected results, such as degraded picture quality or USB connectivity. Refer to <i>SMART installation standards</i> (smarttech.com/kb/171035) for comprehensive information about cables and extensions for SMART hardware products.

Storage and operating requirements

Power requirements	100V to 240V AC, 50 Hz to 60 Hz
Power consumption at 77°F (25°C)	
Standby mode	1.9 W
Normal operating (out-of-box)	131 W
Maximum operating	230 W
Operating temperature	41–95°F (5–35°C)
Storage temperature	-4–140°F (-20–60°C)
Humidity	5–80% relative humidity, non-condensing

Certification and compliance

Regulatory certification	UL (U.S./Canada), FCC, ISED, CE, RCM, PSE
Environmental compliance	
European Union	REACH, RoHS, WEEE and Packaging
U.S.	CONEG Packaging and Conflict Minerals

Purchasing information

Order number	
SBID-6065-HD	SMART Board 6065 HD interactive display with SMART Learning Suite
Optional accessories	
UGK-AM40-EDU	iQ appliance for SMART Board 6000 and 7000 series interactive displays
WM-SBID-501	Fixed wall mount for SMART Board interactive displays
Other	See smarttech.com/accessories
Warranty	Three-year limited equipment warranty
Extended warranty	
EWY1-SBID-6065-HD	One-year warranty extension
EWY2-SBID-6065-HD	Two-year warranty extension

smarttech.com/support
smarttech.com/contactsupport

© 2017 SMART Technologies ULC. All rights reserved. SMART Board, SMART Notebook, SMART lab, SMART amp, SMART response 2, DVIT, Pen ID, Object Awareness, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. iPhone, iPad, iPod touch and Safari are trademarks of Apple Inc., registered in the U.S. and other countries. Google Play, Android and Chrome are trademarks of Google Inc. All other third-party product and company names may be trademarks of their respective owners. This product and/or use thereof is covered by one or more of the following U.S. patents: www.smarttech.com/patents. Contents are subject to change without notice. 09/2017.